

# GEARENCH®

a division of Orbix Corporation

P.O. Box 192 • 4450 S. Hwy. 6  
Clifton, Texas 76634  
(254)675-8651 • fax (254)675-6100  
sales@gearench.com

ISO9001  
Quality  
System  
Certified

## PETOL TANK SAFETY GAUGE INSTALLATION EQUIPMENT CHECKLIST

1. **ALL NECESSARY SAFETY EQUIPMENT**
2. Air Drill, Hoses and 23/64" Pilot Drill Bit
3. Nitrogen preferred for air drill power source – 60 lbs. pressure
4. Ladder, Measuring Tape and Pencil
5. Container to pour oil into PVC collar while drilling hole
6. Medium Sandpaper
7. Chalk Line with Plumb Bob
8. Fiberglass Cloth (Roofing Type) cut in 3-1/2" x 5" pieces. (2 for each strap bracket)
9. Fiberglass resin and catalyst suitable for installation climate
10. 2 part Epoxy Glue
11. Small paint brush to apply resin
12. Matching paint to cover strap brackets and fiberglass on tank
13. Brass hammer and wooden dowel for installing nylon plug into hole in top of tank
14. Crimping tool for attaching sleeves to cable after stringing float and indicator
15. Copper hook used to “grab” cable and pull through hatch when attaching cable to float
16. Caulking gun with 100% silicone cartridge for securing A-Frame and/or Closed Hut
17. Gauge line for measuring fluid level in tank in order to set indicator at proper calibration
18. Masking Tape to secure cable on indicator temporarily until calibration is completed and sleeves are crimped in place
19. Nut Driver or Screw Driver for clamps. Wrenches for 7/16" Hex Nuts on bolted tank installations

SHOULD YOU HAVE ANY QUESTIONS AND/OR COMMENTS, PLEASE FEEL FREE TO CONTACT US AT GEARENCH (254)675-8651 OR FAX (254)675-6100

